

D100 series large character inkjet printer adopts high reliable Drop-On-Demand ink-jet solenoid valve technology. Reliable, strong and durable performance can meet the needs of various industrial coding. The printer can work normally in a variety of harsh environment, such as dusty, wet , vibration environment. The high precision technology makes reliable performance and minimal maintenance.

External Interface



With grade of IP68, the interface not only supports RS232, network interface, but also the count output, information control and other functions.

Print Head

190 mm

Front view

490mm

296mm

Side view

296mm

Screen

Technical Parameters


Printing Parameters

Print Head Duct	3m/ Option 6m
Nozzle Specifications	80u、 120u、 150u
Nozzle Options:	7dots: 5-28m 16dots: 5-64mm
Printing Height	32dots: 5-128mm
Printing Distance	3~30mm
Printing Lines	1~4 lines
Printing Speed	63m/min Max 120/min
Counter	More than 20 independent counters
Ink Color	Black, White, Blue, Green, Yellow, Invisible
Ink Type	MEK based , Water based, Alcohol based, Acetonyl, Pigment
Font	5×6L 7×6L 7×10L 9×8L 9×11L 11×11L 12×12L 16×16L 24×24L 32×32L 11×11B 12×13B 16×16B 24×24B 32×32B
Printing Material	Carton, Plastic, Metal, Boarding, Pipe, Stone, Glass, Electronic components, Industrial chemical packaging, Paint surface and other permeable and non-permeable surface
Print Content	Text,Time, Date(Julian Year), Logo, Shift, SN, Dynamic Barcode/QR Code, Dynamic Serial Data, Dynamic Database(Additional content can be added as required)

Machine Parameters

Operating System	Embedded Linux security operating system
Display Screen	7 inch color display, industrial touch screen
Communication Interface	Network port, USB, RS232
Protection Level	IP65
Power Parameters	Input 100-240V AC
Rated power	150W
Memory	256M
Machine Material	304 stainless steel
Machine Specifications	296mm×296mm×490mm(Length×width×height)
Working Environment	Temperature 0-45°C/ Humidity 30-70%Rh
Related Certification	CE、 RoHS、 FCC
Net Weight	16kg
Main Hardware	American TIAM3358 industrial grade CPU, American Xilinx Spartan-6 industrial grade FPGA
External Interface	Optical sensor, Encoder, Signal light alarm output, Serial number control and transport, External printing information selection and flipped
Support Language	Support more than 40 national languages (Chinese, English, Arabic, Danish, German, Russian, French, Finnish, Korean, Japanese, Spanish, Italian, etc.)

Applications

Wood**Stone****Tires****Textile****Bags****Pipes****Paint Surface**