T220E

HIGH SPEED VARIABLE DATE PRINTING SYSTEM

- Lighter and thinner more flexible
- Network remote centralized management
- Calculate printing costs in real time
- Printing speed up to 406 m/min
- Anti-counterfeiting trace data printing
- Production line alarm light control
- Wireless keyboard and mouse control



More reliable and professional hardware

Use of Cortex-A7 1.2GHz dual core industrial grade processor Self developed industrial grade FPGA. More stable, reliable and anti-interferences in various conditions rendering the printing a unique experience. The print engine uses TIJ dedicated ASIC chip, a perfect match for a variety of original and licensed HP Inks. Professional Cartridge preheat algorithm to ensure optimum print quality at high and low temperatures and environments.

More Powerful and Smarter software

Intelligent embedded Linux operating system provides a professional and more user friendly interface. Embedded powerful drop consumption algorithm that allow instant calculation of cost per print. Powerful variable functions of the 2D Code to meet the today growing customers' demand. Efficient and flexible variable database functions to meet various applications requirements for product traceability.

- Double nozzles seamless stitching and independent installation
- Easily match the weighing machine, packing and paging machine
- Snap-on cartridge, more simple and reliable
- Adjustable inkjet concentration to meet different needs
- Dual phase encoder guarantee high-quality printing
- Support large capacity ink bags and continuous ink supply system
- Multiple brackets along with various installation methods to choose





Technical Parameters

Machine	Body Material	Industrial Stainless steel
	Operating System	Embedded Operating System
	Comm. Interface	Network Interface USB/RJ45 to RS-232
	Working Environment	Max Temp 55C Degrees / Humidity 30 to 70% RH
	Power Supply	30Volts 3Amps DC output
	Dimension Controller	controller: 209mm*122.5mm*61mm/Head Holster 114mm*108mm*54.3mm
	Main Hardware	Cortex-A7 1.2GHz dual core processor industrial grade FPGA chip
	Languages	Italian, English, French, Finnish, Arabic, Danish, German, Russian, Norwegian, Portuguese, Spanish, Japanese.
	External Interface	Photocell, Encoder, External Reverse/Inverse control, Alarm outputs, Serial Number external Reset, External data Selection.
Printing Head	Nozzle Type	Thermally Foamable Head TIJ2.5
	Print Distance	2mm to 5mm
	Print Accuracy	150DPI / 300DPI / 600DPI
	Print Speed	120m/min at 300DPI
	Print Height	Minimum 1mm / Maximum 25.4mm
	Ink Type	Aqueous or Solvent based 42ml Cartridges CIS S
	Ink Color	Black, White, Red, Yellow, Blue, Green, Stealth, UV readable
	Cartridge Chip	Contactless RFID tags for automatic identification and recording ink parameters and consumptions
	Printable Substrates	Cardboard, Plastic, Metal, Cables, Electronic components, Auto Parts, Industrial Chemical packaging, Pharmaceuticals and more.
	Print Contents	Multi language Characters, 2DCode, Barcodes, Images, Serial Numbers, Date, Counters, Variable Database, RS232 to receive real data to print









Packing carton

Medicine

Furniture and wood

Food packaging

PET plastics











GS1 Data Matrix

Dynamic security barcode

Multi-group printing

HD bold font

Multi-dot font



0-2170-8051 www.contechsupply.co.th contech@contechsupply.co.th



