

T600

HIGH SPEED VARIABLE DATE PRINTING SYSTEM

TEKKON

- ◆ WIRELESS KEYBOARD AND MOUSE CONTROL
- ◆ FLEXIBLE AND EFFICIENT SPLICING MODE
- ◆ CALCULATE PRINTING COSTS IN REAL TIME
- ◆ ANTI-COUNTERFEITING TRACE DATA PRINTING
- ◆ GS1 INTERNATIONAL MEDICINE MONITOR CODE



◆ MORE RELIABLE AND PROFESSIONAL HARDWARE

Use of the American TI's AM3358 Industrial Grade CPU Xilinx Spant6 Industrial Grade FPGA. More stable, reliable and anti-interferences in various conditions rendering the printing a unique experience. The print engine uses TIJ dedicated ASIC chip, a perfect match for a variety of original and licensed HP Inks. Professional Cartridge preheat algorithm to ensure optimum print quality at high and low temperatures and environments.

◆ MORE POWERFUL AND SMARTER SOFTWARE

Intelligent embedded Linux operating system provides a professional and more user friendly interface. Embedded powerful drop consumption algorithm that allow instant calculation of cost per print. Powerful variable functions of the 2D Code to meet the today growing customers' demand. Efficient and flexible variable database functions to meet various applications requirements for product traceability.



Contech Supply

- ◆ SUPPORT UP TO 6 SENSORS, CONFIGURE THE TRIGGER MODE AT WILL
- ◆ MAXIMUM SUPPORT 6 PRINT HEADS, THE NUMBER OF A PRINT HEAD CAN BE CONFIGURED
- ◆ TWO ROWS OF NOZZLES ALTERNATE MODE TO EXTEND INK CARTRIDGE LIFE
- ◆ MULTIPLE SPLICING MODES WITH A MAXIMUM PRINTING HEIGHT OF 76.2MM
- ◆ 10-INCH INDUSTRIAL TOUCH SCREEN BRINGS EXCELLENT HUMAN INTERACTION EXPERIENCE
- ◆ STEPLESS FREQUENCY CONVERSION FUNCTION, THE PRINT WIDTH CAN BE ADJUSTED AT WILL
- ◆ ANTI-COLLISION REBOUND ASSEMBLY TO PREVENT ACCIDENTAL DAMAGE TO THE PRINT HEAD



Technical Parameters

| | | |
|----------------|---|---|
| Printing | Print Distance | 2mm to 3mm |
| | Nozzle Type | Thermally Foamable Head TIJ2.5 |
| | Print Height | Minimum 1mm / Maximum 76.2mm |
| | Ink Type | Aqueous or Solvent based 42ml Cartridges CIS S |
| | Print Accuracy | Vertical :100DPI / 150DPI / 300DPI Horizontal:40~2400DPI |
| | Ink Color | Black, White, Red, Yellow, Blue, Green, Stealth, UV readable |
| | Print Speed | 152.4 M/min at 300DPI, 304.8M/min at 150DPI, 381M/min at 120DPI, 508M/min at 90DPI |
| | Cartridge Chip | Contactless RFID tags for automatic identification and recording ink parameters and consumptions |
| | Printable Substrates | Cardboard, Plastic, Metal, Cables, Electronic components, Auto Parts, Industrial Chemical packaging, Pharmaceuticals and more |
| Print Contents | Multi language Characters, 2DCode, Barcodes, Images, Serial Numbers, Date, Counters, Variable Database, RS232 to receive real data to print | |
| Machine | Body Material | Industrial Stainless steel |
| | Operating System | Embedded Linux operating system |
| | Power Supply | 110 - 230 Volts AC 50-60Hz input |
| | Communication Interface | Network Interface USB/RJ45 to RS-232, TCP/IP |
| | Working Environment | Max Temp 55C Degrees / Humidity 30 to 70% RH |
| | Dimension | Controller 274mm x 165.4mm x 88mm / Head Holster 112mm x 79mm x 103mm |
| | Main Hardware | American TI A M3358 industrial grade CPU/USA Xilinx Spant6 industrial grade FPGA / TIJ dedicated ASIC chip |
| | External Interface | Photocell, Encoder, External Reverse/Inverse control, Alarm outputs, Serial Number external Reset, External data Selection |
| | Supported Languages | Italian, English, French, Finnish, Arabic, Danish, German, Russian, Norwegian, Portuguese, Spanish, Japanese... |



Packing carton



Medicine



Furniture and wood



Food packaging



PET plastics



GS1 Data Matrix



Dynamic security barcode



Multi- group printing



HD bold font



Multi-dot font



02-170-8051



contech@contechsupply.co.th



www.contechsupply.co.th



@contechsupply